



Product of India

# SOLID RESILIENT TYRES



# SUNBEAR

<b>SUNBEAR</b>	<b>E4</b>
<b>Grade</b>	<b>PREMIUM ECONOMY</b>
<b>Design</b>	<b>2-stage Rich Natural Rubber tread, Heat stabilized centre area</b>
<b>Ride</b>	<b>Firm to Normal</b>
<b>Operating Conditions</b>	<b>Up to 15 hours per day, intermittently</b>
<b>Advantages</b>	<b>Unique design, Exceptional performance for price, Ride comfort</b>

<b>TYRE SPECIFICATIONS</b>								
<b>TYRE SIZE</b>	<b>TYRE SIZE (METRIC)</b>	<b>RIM</b>	<b>TREAD</b>	<b>Tyre dimensions in mm</b>			<b>Load capacity on fork lifts, kg at 25kmph</b>	
				<b>Outer Dia.</b>	<b>Sidewall width</b>	<b>Tread width</b>	<b>Load wheel</b>	<b>Steer wheel</b>
3.00 - 4		2.10	RIB	245	85	75	260	195
3.50 - 4		2.10	RIB	250	89	83	260	195
4.00 - 4		2.50	LUG	300	92	84	535	412
3.50 - 5		3.00	RIB	300	100	90	900	690
	140/55-6	4.50	LUG					
4.00 - 8		2.75, 3.00	LUG, RIB	402	103	86	950	730
4.00 - 8		3.75	RIB	405	119	86	950	730
12x3 1/2 - 8		3.00	SM	308	98	87	850	650
	100/80-8	2.50	SM	360	105	90	1,000	770
15X4 1/2 - 8	125/75-8	3.00, 3.25	LUG	368	105	90	1,040	800
15X4 1/2 - 8	125/75-8	3.00, 3.25	SM	378	110	100	1,040	800
5.00 - 8		3.00	LUG	450	120	110	1,415	1,090
5.00 - 8		3.75	RIB	450	125	110	1,415	1,090
16X6 - 8	150/75-8	4.33	LUG	406	140	125	1,270	975
17X7 - 8		4.33	SM	430	150	134	2,000	1,540
18X7 - 8	180/70-8	4.33	LUG	450	157	142	2,145	1,650
	140/55 - 9	4.00	LUG	376	125	110	1,170	900
6.00 - 9		4.00	LUG	520	138	120	1,885	1,450
21X8 - 9	200/75-9	6.00	LUG	517	188	157	2,755	2,120
	200/50 - 10	6.50	LUG	454	190	160	2,470	1,900
6.50 - 10		5.00, 5.50	LUG	566	160	140	2,340	1,800
7.50 - 10		5.00, 5.50	LUG	630	170	150	3,070	2,360
23X9 - 10	225/75-10	6.50	LUG	580	194	178	3,160	2,430
7.00 - 12		5.00	LUG	646	172	150	2,920	2,240
23X10 - 12		8.00	LUG	580	232	200	3,770	2,900
27X10 - 12	250/75-12	8.00	LUG	672	240	200	3,900	3,000
23X5 - 13		3.75	LUG	605	122	102	1,495	1,150
7.00 - 15		5.50	LUG	705	180	158	3,545	2,725
7.50 - 15		5.50, 6.00, 6.50	LUG	736	193	168	3,900	3,000
8.15-15 (28X9-15)	225/75-15	7.00	LUG	678	221	190	3,445	2,650
8.25 - 15		6.50	LUG	808	192	173	4,750	3,650
2.50 - 15	250/70-15	7.00, 7.50	LUG	706	220	190	4,745	3,650
3.00 - 15	315/70-15	8.00	LUG	806	242	223	5,850	4,500

28X12.5-15	345/45-15	9.75	LUG	705	275	255	5,525	4,250
	355/65-15	9.75	LUG	810	285	265	7,000	5,450
	400/60-15	11.00	LUG	810	318	298	8,970	6,900
6.50 - 16		5.50	SM					
7.50 - 16		5.50, 6.00, 6.50	LUG	736	193	168	3,900	3,000
8.25 - 16		5.50, 6.00	LUG	808	192	173	4,750	3,650
7.50 - 20		6.00	LUG	870	200	175	3,900	3,250
8.25 - 20		6.50	LUG	915	200	180	4,380	3,650
	355/50 - 20	10.00	SM	810	285	265	8,970	6,900
9.00 - 20		6.50, 7.00	LUG	972	226	191	5,400	4,500
10.00 - 20		7.00, 7.50, 8.00, 8.50	LUG	1,004	250	203	6,000	5,000
10.00 - 20		7.50, 8.00, 8.50	SM	1,050	265	235	6,000	5,000
10.00 - 20		8.00	SCR					
11.00 - 20		7.50, 8.00, 8.50	SM	1,050	265	235	6,000	5,000
12.00 - 20		8.00, 8.50	LUG	1,080	255	232	7,560	6,300
12.00 - 20		8.00, 8.50	SM	1,140	295	250	7,560	6,300
13.00 - 20		8.00, 8.50	SM	1,140	295	250	7,560	6,300
12.00 - 24		8.50, 10.00	LUG	1,165	265	230	8,040	6,700
14.00 - 24		10.00	LUG	1,275	308	270	11,100	9,250
14.00 - 25		10.00	LUG	1,275	308	270	11,100	9,250

**All dimensions are nominal and we reserve the right to make changes any time without notice**

**Available in Black and Non Marking treads, with or without Clip.**

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_